



PRODUCT SPECIFICATIONS

Product Dimensions	Overall Thickness	2.5 mm
	Width and Length	6" W x 48" L, 12" W x 24" L
Packaging (Per Carton)	18 Planks	36 SF
Construction	Top Layers	High-Definition Decor Film – Wood or Stone (EIR)
		Ceramic Quartz-Enhanced Acrylic Coating— EPA Reg. Bacteriostatic
		20 Mil Wear Layer
	Core	Fiberglass Reinforced Core (FRC) - 100% Virgin Material
	Density	≥ 4.2 Kg/m3
	Pad	No Pad
	Bevel	No Bevel
Installation	Glue-Down	
Under Floor Heating	Approved - See installation manual for details.	
Warranty	30 Years Residential/25 Years Light Commercial/20 Years Commercial	
Test Data		
Static Load	NALFA ANSILF-01-2011	250psi Class 4, Heavy Commercial
Heat Exposure Resistance F1700	ASTM F2199 EN16511	0.03% Class 34, Heavy Commercial
Swelling after submersion	NALFA LF 01-2011	0% Class 4, Heavy Commercial
Fire Rating	ASTM E648/ 662	Class I
Wear Resistance	NALFA LF 01-2011	Class 4, Heavy Commercial
Residual Indentation F1700	ASTM F1914 EN 16511	Pass Class 34, Heavy Commercial
Impact Resistance (Big Ball)	NALFA LF01-2011 EN 16511	Class 4, Heavy Commercial IC3, Class 34, Heavy Commercial
Impact Resistance (Small Ball)	NALFA LF01-2011 EN 16511	Class 4, Heavy Commercial IC3, Class 34, Heavy Commercial
Slip Resistance	ASTM D2047	>0.5, Meets ADA
Resistance to staining F1700	ASTM F925 NALFA LF01-2011	Pass Class 4, Heavy Commercial
Chemical Composition		
VOC	FloorScore™	Pass California 01350

Ortho-phthalates	Prop 65	Not Detected / In Compliance
Lead	CPSIA	None Detected
Substances of Very High Concern (SVHC) (Mercury, Chromium VI, Cadmium, SCCP, Benzene, Xylene, Tributyltin, etc.)		Not Detected / REACH Compliant

LEED SCORECARD					
LEED PROGRAM CERTIFICATION	CATEGORY	CREDIT TITLE	LEED POINTS ATTAINABLE	CREDIT DESCRIPTION	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
BD + C Building Design and Construction Applies to buildings that are being newly constructed or going through a major renovation; includes New Construction, Core & Shell, Schools, Retail, Hospitality, Data Centers, Warehouses & Distribution Centers, and Healthcare	Indoor Environmental Quality	Credit 1: Enhanced Indoor Air Quality Strategies - Option 2 Additional Enhanced IAQ Strategy - Option D	1 Point ID&C 2 Points Retail CI	To reduce concentrations of chemicals that can damage air quality, human health, productivity, and the environment.	1. Formaldehyde emissions are less than 0.05mg/m3, TVOCs are less than 0.5mg/m3. 2. The product is FloorScore™ certified.
		Credit 2: Low-Emitting Materials - Option 1 Flooring	1 Point		1. VOC emissions are less than 0.5mg/m3. 2. The product is FloorScore™ certified.
		Credit 4: Indoor Air Quality Assessment - Option 2 Air Testing	2 Points	To establish better quality indoor air in the building	1. Formaldehyde emissions and TVOCs are less than 0.05mg/m3. 2. The product is FloorScore™ certified.
		Credit 9: Acoustic Performance	2 Points	To provide effective acoustic design	The product has a high acoustic performance. IIC and STC test reports are available on request.
	Material & Resource	Credit 4: Material ingredient - Option 2	1 Point	Minimize the use and generation of harmful substances	The product is 100% REACH compliant
		Credit 6 - PBT source reduction: Lead, Cadmium and Copper	1 Point	To reduce the release of persistent, bioaccumulative, and toxic chemicals	The product is free of lead, cadmium and copper
O + M Building Operations and Maintenance	Material & Resource	Credit 3: Purchasing - Facility maintenance and renovation	1 Point	To reduce the environmental harm from materials used in building renovations	1. The product is 100% REACH compliant. 2. Formaldehyde emissions and TVOCs are less than 0.05mg/m3. 3. The product is FloorScore™ certified.
HOMES Applies to single family homes, low-rise multi-family (one to three stories), or mid-rise multi-family (four to six stories).	Indoor Environmental Quality	Credit 2: Containment Control - Option 4 Air Testing	1 Point	Demonstrate that contaminants do not exceed concentration levels listed	The product is FloorScore™ certified.
	Material & Resource	Credit 7: Low-Emitting Materials	0.5 Point	To reduce occupant's exposure to airborne chemical contaminants	The product is FloorScore™ certified and meets the requirements of CA Section 01350. The product is made with ULEF or non-added formaldehyde material
ID & C Interior Design and Construction Applies to projects that are a complete interior fit-out; includes Commercial Interiors, Retail and Hospitality.	Indoor Environmental Quality	Credit 1: Enhanced Indoor Air Quality Strategies - Option 2 Additional Enhanced IAQ Strategies - Option D	1 Point ID&C 2 Points Retail CI	To reduce concentrations of chemical contaminants that can damage air quality, human health, productivity, and the environment.	1. Formaldehyde emissions and TVOCs are less than 0.05mg/m3. 2. The product is FloorScore™ certified.
		Credit 2: Low-Emitting Materials - Option 1 Flooring	1 Point		1. VOC emissions are less than 0.5mg/m3. 2. The product is FloorScore™ certified.
		Credit 4: Indoor Air Quality Assessment - Option 2 Air Testing	2 Points	To establish better quality indoor air in the building	1. Formaldehyde emissions and TVOCs are less than 0.05mg/m3. 2. The product is FloorScore™ certified.
		Credit 9: Acoustic Performance	2 Points	To provide workspaces and classrooms effective acoustic design	The product has a high acoustic performance. IIC and STC test reports are available on request.
	Material & Resource	Credit 4: Material ingredient - Option 2	1 Point	Minimize the use and generation of harmful substances	The product is FloorScore™ certified.

WELL SCORECARD

The WELL Building Standard is founded on the understanding that facets of our environment interact with personal, genetic and behavioral factors to shape our overall health and well-being. By compiling leading practices in building design and management and referencing existing standards and best practice guidelines set by governmental and professional organizations, WELL works to harmonize and clarify existing thresholds and requirements.

AIR

Feature 01. Air Quality Standards

REQUIREMENT	CONCEPT SCORE	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
Part 1. Standards for Volatile Substances	PRECONDITION	<ul style="list-style-type: none"> a. Formaldehyde emissions are less than 0.05mg/m3 b. Total volatile organic compounds less than 500ug/m3 (0.5mg/m3)

Feature 04. VOC Reduction

REQUIREMENT	CONCEPT SCORE	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
Part 1. Interior Paints and Coatings	PRECONDITION	<ul style="list-style-type: none"> The VOC limits of newly applied paints and coatings meet one of the following requirements: <ul style="list-style-type: none"> a. 100 % of installed products meet California Air Resources Board (CARB) 2007, Suggested Control Measure (SCM) for Architectural Coatings, or South Coast Air Quality Management District (SCAQMD) Rule 1113, effective June 3, 2011, for VOC content. a. The VOC limits for California Air Resources Board (CARB) are less than 0.11ppm. b. Measured Concentration of Total Volatile Organic Compounds (TVOC): Less than/equal to 0.5 mg/m3 (in compliance with CDPH/EHBL Standard Method v1. 1-2010). <p>The product is FloorScore™ certified.</p>
Part 3. Flooring	PRECONDITION	<p>The VOC emissions of all newly installed flooring must meet all limits set by the following, as applicable:</p> <ul style="list-style-type: none"> a. California Department of Public Health (CDPH) Standard Method v1. 1-2010. <p>Conforms to the CDPH/EHBL Standard Method v1. 1-2010 (California Section 01350), effective January 1, 2012, for the school classroom and private office parameters when modeled as Flooring.</p> <p>The product is FloorScore™ certified.</p>

Feature 11. Fundamental Material Safety

REQUIREMENT	CONCEPT SCORE	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
Part 1. Asbestos and Lead Restriction	PRECONDITION	<ul style="list-style-type: none"> All newly installed building materials meet the following materials composition requirements: <ul style="list-style-type: none"> a. No asbestos. b. Not more than 100 ppm (by weight) added lead. a. No asbestos. b. The product contains less than 100 ppm.
Part 2. Lead Abatement	PRECONDITION	The product contains less than 90 ppm.
Part 3. Asbestos Abatement	PRECONDITION	The product contains less than 90 ppm.

Feature 25. Toxic Material Reduction

REQUIREMENT	CONCEPT SCORE	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
Part 2. Flame Retardant Limitation	OPTIMIZATION	The product does not contain halogenated flame retardants

Part 3. Phthalate (Plasticizers) Limitation	DEHP, DBP, BBP, DINP, DIDP or DNOP (often found in polyvinyl chloride [PVC]) are limited in the following components to 0.01% (100 ppm): a. Flooring, including resilient and hard surface flooring and carpet. b. Wall coverings, window blinds and shades, shower curtains, furniture, and upholstery. c. Plumbing pipes and moisture barriers.	OPTIMIZATION	In accordance with US Consumer Product Safety Improvement Act 2008 (CPSIA) (H.R.4040) Title I, Section 108 & California Proposition 65 & Annex XV II item 51 & 52 of the REACH Regulation (EC) No. 1907/2006 and amendment No. 552/2009, the product contains less than 100ppm.
Part 5. Urea-Formaldehyde Restriction	Urea-formaldehyde presence is limited in the following components to 100 ppm: a. Furniture or any composite wood products. b. Laminating adhesives and resins. c. Thermal insulation.	OPTIMIZATION	The product contains urea-formaldehyde less than 100ppm.
COMFORT			
Feature 74. Exterior Noise Intrusion			
REQUIREMENT		CONCEPT SCORE	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
Part 1. Sound Pressure Level	Each regularly occupied space meets the following sound pressure level as measured when the space and adjacent spaces are unoccupied, but within 1 hour of normal business hours: a. Average sound pressure level from outside noise intrusion does not exceed 50 dBA.	PRECONDITION	1. The product has IIC = 66 according to the standard ASTM E492-09
Feature 79. Internally Generated Noise			
REQUIREMENT		CONCEPT SCORE	HOW OUR PRODUCTS CONTRIBUTE TO OBTAIN LEED POINTS
Part 1. Sound Masking Limits	If sound masking systems are used, sound levels fall within the following range, when measured from the nearest workspace: a. Open workspaces: 45 - 48 dBA. b. Enclosed offices: 40 - 42 dBA	OPTIMIZATION	1. The product has IIC = 66 according to the standard ASTM E492-09